

Urovo

UROVO DT630

Specifications





1. Specifications

Performance	Model	UROVO DT630
	O.S.	Android 15.0, GMS/AER
	Processor	Octa-core 2.5 GHz
	Memory	RAM: 8GB, ROM: 128GB
	Extended memory	Micro SD card, Support up to 2 TB
Basic Specifications	Dimensions	170.5mm x 78.1mm x 10.4mm
	Weight	240g (with standard battery)
	Display	6.58 inch display, 1080*2408
	Touch Screen	Ultra sensitive capacitive touch panel, support multi-touch, works with gloves and wet fingers
	Main battery	Standard battery: 3.85V 4500mAh
	Charging time	9V2A, less than 2.5h (room temperature)
	Buttons	power button, Vol +/- button, Scan button*2
	Camera	Front: 8MP FF, Rear: 50MP PDAF, Support Flash
	Sensors	Light + Accelerator + Proximity + Geomagnetic + Gyro
	Fingerprint	Support
	Scanning	Professional scan engine Support international standard 1D/2D barcode; Support barcode displayed on screen
	Slots	Nano- SIM x 1, Micro SD x 1
	Audio	2 microphones, 1 for noise cancellation; 1 speaker
	Interfaces	USB Type-C: OTG, USB 3.1, DP
RFID	NFC	ISO 14443 Type A and B; Sony FeliCa and ISO 15693 cards; Card Emulation via Host; Contactless payment support; ECP1.0 and ECP2.0 polling support; Apple VAS certified; MIFARE 1K/4K, MIFARE DESFire, ISO/IEC 18092 (Type F)
	UHF	Protocol: EPC C1 GEN2/ISO18000-6C
		Frequency: 902-928MHz/865-868MHz
		Reading Range:1.2m Reading speed: 50 tags/s
Network Connections	Location	GPS, A-GPS, BEIDOU, GLONASS, Galileo, QZSS
	WWAN	5G/4G/3G/2G
	Bluetooth	BT5.4 + BR/EDR + BLE
	Wi-Fi	Wi-Fi 6E, 2.4G/5G/6Ghz, 2*2 MU-MIMO IEEE 802.11a/b/g/n/ac/d/h/i/k/r/v/w/mc/ax
Environment	Operating Temp.	-20°C to 60°C
	Storage Temp.	-40°C to 70°C
	Humidity	5%RH ~ 95%RH (Non-condensing)
	Drop	1.5m



	Specification	1.8m with case
	Tumbling	0.5m 1000 times
	Sealing	IP68
	ESD	Air +/-15 kV, Contact +/-8 kV